SU



SDAC-TR-79-4



EVALUATION OF LOCATION ACCURACY USING P_n AND P_g ARRIVALS

A. C. Chang and D. P. J. Racine
Seismic Data Analysis Center
Teledyne Geotech, 314 Montgomery Street, Alexandria Virginia 22314

30 MAY 1980

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED.

Sponsored by

The Defense Advanced Research Projects Agency (DARPA)


DARPA Order No. 2551

Monitored By AFTAC/VSC

312 Montgomery Street, Alexandria, Virginia 22314



D



Disclaimer: Neither the Defense Advanced Research Projects Agency nor the Air Force Technical Applications Center will be responsible for information contained herein which has been supplied by other organizations or contractors, and this document is subject to later revision as may be necessary. The views and conclusions presented are those of the authors and should not be interpreted as necessarily representing the official policies, either expressed or implied, of the Defense Advanced Research Projects Agency, the Air Force Technical Applications Center, or the US Gevernment.

REPORT DOCUMENTATION PAGE	READ INSTRUCTIONS BEFORE COMPLETING FOR
	NO. 3. RECIPIENT'S CATALOG NUMBER
SDAC-TR-79-4 (A D- A O 9	15 876
	5. TYPE OF REPORT & PERIOD COVE
4. TITLE (and Subtitle)	C E
EVALUATION OF LOCATION ACCURACY USING	7 Technical reptis
PM and PM ARRIVALS.	6 PERFORMING ORG. REPORT NUMB
7. AUTHOR(e)	8. CONTRACT OR GRANT NUMBER(s)
A. C./Chang	75)
D. P. J./Racine	F08606-79-C-0007
	DARPA ON der-200
9. PERFORMING ORGANIZATION NAME AND ADDRESS	10. PROGRAM ELEMENT, PROJECT, T
Teledyne Geotech	
314 Montgomery St.	VT/9709
Alexandria, Virginia 22314	
11. CONTROLLING OFFICE NAME AND ADDRESS	11 30 May 1980
Defense Advanced Research Projects Agency	13 NUMBER OF PAGES (14.4
Nuclear Monitoring Research Office 1400 Wilson Blvd., Arlington, Virginia 22209	20 (/2)2.
14. MONITORING AGENCY NAME & ADDRESS(II different from Controlling Office	ice) 15. SECURITY CLASS. (of this report)
VELA Seismological Center	10% 102000000
312 Montgomery Street	Unclassified
Alexandria, Virginia 22314	15. DECLASSIFICATION DOWNGRAD
APPROVED FOR PUBLIC RELEASE; DIS	INIBOTION CALIFIEDS
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different	ent from Report)
18. SUPPLEMENTARY NOTES	
19. KEY WORDS (Continue on reverse side if necessary and identify by block no	umber)
	- 6
Location Accuracy (Psu	bg) (Psubn)
Location with P, P	3401)
n g	
	(mber)
an annual Continue or severe side if necessary and identify by block no	
20. RESTRACT (Continue on reverse side if necessary and identify by block no	
20. ABSTRACT (Continue on reverse side if necessary and identify by block not Seismic event locations obtained by using severe errors because the Earth's crust is late	and arrivals may cause

for each station to be assigned an appropriate model. Travel times for each

DD 1 JAN 73 1473 EDITION OF 1 NOV 65 IS OBSOLETE

Inclassified 40823 8 &


SECURITY CLASSIFICATION OF THIS PAGE(When Date Entered)


phase are computed by using the selected earth model and the specified phase.

The merit of this method is evaluated by relocating 12 explosions in the western United States. When each station model was chosen individually from a number of regional models, location errors were slightly larger than errors using only one (regional) model for all stations. However, errors were reduced when each station was assigned its own model from a set of finely localized crustal models.

Errors were also reduced when the local crustal model appropriate to the source region was used for all stations. This suggests that a crustal model for the source and a separate model for each station would result in even better locations.

The addition of parrivals to the set of arrivals reduced location error by about 30%. However, the difference is not great enough for this small sample but we can be sure that it is significantly different from zero.





EVALUATION OF LOCATION ACCURACY USING

 P_n and P_g ARRIVALS

SEISMIC DATA ANALYSIS CENTER REPORT NO.: SDAC-TR-79-4

AFTAC Project Authorization No.:

VELA T/9709/B/ETR

Project Title:

Seismic Data Analysis Center

ARPA Order No.:

2551

Name of Contractor:

TELEDYNE GEOTECH

Contract No.:

F08606-79-C-0007

Date of Contract:

01 October 1979

Amount of Contract:

\$279,929

Contract Expiration Date:

30 September 1980

Project Manager

Robert R. Blandford

(703) 836-3882

P.O. Box 334, Alexandria, Virginia 22313

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED.

ABSTRACT

Seismic event locations obtained by using P_g and P_n arrivals may cause severe errors because the Earth's crust is laterally heterogeneous. Location errors are attributed to the fact that crustal velocities and thicknesses for each source-to-station path are different from those of the standard crustal model used in the location program. To overcome this difficulty, we have installed a number of crustal models in a location program and made it possible for each station to be assigned an appropriate model. Travel times for each phase are computed by using the selected earth model and the specified phase.

The merit of this method is evaluated by relocating 12 explostions in the western United States. When each station model was chosen individually from a number of regional model., location errors were slightly larger than errors using only one (regional) model for all stations. However, errors were reduced when each station was assigned its ow. model from a set of finely localized crustal models.

Errors were also reduced when the local crustal model appropriate to the source region was used for all stations. This suggests that a crustal model for the source and a separate model for each station would result in even better locations.

The addition of $\frac{P}{g}$ arrivals to the set of $\frac{P}{n}$ arrivals reduced location error by about 30%. However, the difference is not great enough for this small sample but we can be sure that it is significantly different from zero.

TABLE OF CONTENTS

	Page
ABSTRACT	3
LIST OF FIGURES	5
LIST OF TABLES	6
1. INTRODUCTION	7
2. METHOD OF INVESTIGATION	8
2.1 The Location Program	8
2.2 Crustal Models and Their Usage	8
2.3 Data	12
2.4 List of Location Experiments	12
3. DISCUSSION	14
3.1 Location Accuracies with P and P $_{ m g}$	14
3.2 Summary and Suggestions for Further Work	17
ACKNOWLEDGEMENTS	19
REFERENCES	20

LIST OF FIGURES

Figure No.	Title	Page
1	Regions based on seismic properties (after Pakiser and Robinson, 1966).	9
2	Southwestern United States local crustal models.	10

LIST OF TABLES

rable No.	Title	Page
I	Comparison of Crustal Structures.	11
ΙŢ	List of Events.	13
111	Location Errors, KM.	15
1v	Origin Time Errors, Sec, (T _{calc} - T _{true}).	16

1. INTRODUCTION

The accuracy of event location depends strongly upon the variation of crustal structures from the seismic source to each station. We have devised a method to minimize the effect of crustal variations by using various crustal models for each source-to-station path.

Chiburis and Ahner (1970) studied the location accuracy of 28 Nevada Test Site explosions using teleseismic P arrivals. They showed that the location accuracy of these events (depth restrained) averaged about 7.66 kilometers but could be as large as 20 kilometers. They repeated the relocation of those events with station corrections and location errors were reduced to about 2.81 kilometers. However, Chiburis and Ahner cautioned that the set of station corrections for the Nevada Test Site was applicable only to a small region.

Location accuracies resulting from using P arrivals at local stations were investigated by Engdahl and Lee (1976). Three methods were compared in that study. The first method was HYPO71 (Lee and Lahr, 1972), where a uniformly layered crustal model was used. The second method was HYPO74, where different crustal models, as well as station corrections, were used for each individual station. The third method used a complex two-dimensional model to describe crustal variations across the San Andreas fault near Bear Valley. Travel times for each station in the third method were computed by a ray tracing method. Although the third method is the most elaborate one, improvements in location accuracies over the second method appeared to be small. All stations used in their study were within 30 kilometers of the epicenter.

Chiburis, E. F. and R. O. Ahner (1970). A seismic location study of station anomalies, network effects, and regional bias at the Nevada Test Site, Teledyne Geotech, Seismic Data Laboratory Report No. 253, Alexandria, VA.

Engdahl, E. R. and W. H. K. Lee (1976). Relocation of local earthquakes by seismic ray tracing, <u>J. Geophys. Res.</u>, <u>81</u>, 4400-4406.

Lee, W. H. K. and J. C. Lahr (1975). HYPO71 (Revised): A computer program for determining hypocenter, magnitude, and first motion pattern of local earthquakes, USGS Open-file report 75-311, Menlo Park, CA.

METHOD OF INVESTIGATION

2.1 The Location Program

The location program used in this project was originally developed by Julian (1974). McCowan (1978) modified it and installed an option to compute travel times for six crustal phases, P_n , P^* , P_g , S_n , S^* , and S_g , from a crustal model (Jeffreys-Bullen model). We modified the program to allow it to use up to fifty crustal velocity models. Furthermore, the program was modified such that each station can use an independent model to compute travel times.

2.2 Crustal Models and Their Usage


Figure 1 shows the boundaries and codes for ten regional crustal models published by Pakiser and Robinson (1966), of which numbers 1 through 7 are used in this investigation. In Figure 2, fifteen more localized crustal models in the southwestern United Scates (SWUS) are shown. In addition to those models, crustal models for Herrin 68 and Jeffreys-Bullen are also available in the program. Table I is a comparative listing of these models.

The input to the location program must identify the station, signal phase, and the crustal model to be used for this station. To identify the crustal model the analyst must make a preliminary location of the source and, with Figures 1 and 2, decide for each station on the best overall model for the path from the source to the station. Although this scheme provides versatility, it is sometimes difficult to choose a model, as a particular source—to—receiver station path may travel across regions best described by several different models. In such a case the analyst may opt to choose an average model, such as the Herrin model, for this station.

Julian, B. (1973). Extension of standard event location procedures, Seismic Discrimination SATS, Lincoln Laboratory, M.I.T., 30 June 1978, 4-9.

McCowan, D. W. (1978). Personal communication.

Pakiser, L. C. and R. Robinson (1966). Composition of the continental crust as estimated from seismic observations, The Earth Beneath the Continents, American Geophysical Union, Geophysical Monograph # 10, 620-626.



Regions based on seismic properties (after Pakiser and Robinson, 1966). \clubsuit Event locations. Figure 1.




Figure 2. Southwestern United States local crustal models locations.

Мо	del	1st l	Layer	2nd	Mantle	
Area	Designator	Thickness	Velocity	Thickness	Velocity	Velocity
General:						1
Jeffreys-Bullen	J-B	15.00	5.57	18.00	6.50	7.80
Herrin 68	HE	15.00	6.00	25.00	6.75	8.05
Regional:						
Calif. Coast	ccus	15.00	6.20	5.00	7.00	8.10
Sierra Nevada	SNUS	25.00	6.20	25.00	7.00	7.90
Pac. NW Coast	PCUS	10.00	6.20	25.00	7.00	7.70
Columbia Plat.	CAUS	10.00	6.20	35.00	7.00	7.90
Basin & Range	BRUS	20.00	6.20	10.00	7.00	7.90
Colorado Plat.	CPUS	25.00	6.20	15.00	7.00	7.80
Rocky Mtns.	RMUS	25.00	6.20	15.00	7.00	8.00
Local:						
N. Calif.	NOCA	12.00	5.60	18.00	6.70	8.00
Coast Calif.	COCA	10.00	5.60	10.00	6.70	8.00
Sierra Nevada	SNCA	15.00	6.00	20.00	6.50	7.60
S. Calif.	SOCA	20.00	6.20	10.00	6.90	7.80
N. Nevada	NONV	20.00	6.00	10.00	6.70	7.90
Cent. Nevada	CENV	20.00	6.00	10.00	6.60	7.80
SW Nevada	SWNV	27.00	6.20	9.00	7.10	7.80
Lake Mead Nev.	LMNV	15.00	6.00	15.00	6.50	7.90
W. Utah	WEUT	15.00	5.90	10.00	6.40	7.40
E. Utah	EAUT	27.00	6.20	13.00	6.80	7.80
N. Arizona	NOAZ	26.00	6.00	12.00	6.80	7.80
Cent. Arizona	CEAZ	19.00	6.00	12.00	6.70	7.90
S. Arizona	SOAZ	15.00	6.00	7.00	7.00	7.80
W. Colorado	WECO	9.00	6.00	31.00	6.60	7.80
W. New Mexico	WENM	19.00	6.20	21.00	6.50	7.90

2.3 Data

Twelve nuclear explosions were used as the data base. Of these events seven were at the Nevada Test Site (NTS) and six others were located in Colorado, New Mexico and Nevada.

 P_n and P_g arrivals for four events were picked by analysts at the Seismic Data Analysis Center with cross checks to the published shot reports for each event. For the rest of the events, phase arrivals as reported in the shot reports were used. Reading errors of P_n and P_g are greater than errors for teleseismic P. P_n and P_g (especially P_g) signal waveforms are very complex and often emergent. In Table II we list the event parameters, numbers of P_n and P_g arrivals, and the data sources for the events used.

2.4 List of Location Experiments

In the following test categories events were relocated using (a) P_n and P_g phases, (b) P_n only, and (c) P_g only:

- 1) Local station models;
- 2) Regional station models;
- 3) Herrin 68;
- 4) Epicenter models; and
- 5) Jeffreys-Bullen.

The Jeffreys-Bullen model was not tested with P_n only, because large residual times were observed using this model. Location errors using P_g only were so large that it was eliminated from further analysis. It was necessary to restrict the event depth to zero in all tests, because the hypocenter depth may go deeper than the crustal thickness during iterations in which case P_n and P_g travel times can not be computed.

TABLE II List of Events

Name	°LAT	°LON	Date	Origin Time	# of P n	# of P g	Data Source	Remarks
PASSAIC	37.1N	116.0W	06 Apr 62	18:00:00.1	4	3	Alex Labs	
DORMOUSE	37.0N	116.0W	05 Apr 62	18:00:00.1	3	4	Alex Labs	
BANDICOOT	37.0N	116.0W	19 Oct 62	18:00:00.1	6	5	Alex Labs	
ROANOKE	37.2N	116.0W	12 Oct 62	15:00:00.1	4	4	Alex Labs	
KLIKITAT	37,2N	116.0W	20 Feb 64	15:30:00.1	13	12	Shot Report	
MERRIMAC	37.1N	116.0W	13 Feb 62	16:00:00.2	8	0	Shot Report	
FAULTLESS	38.6N	116.2W	19 Jan 68	18:15:00.1	5	5	Shot Report	
SHOAL	39.2N	118,4W	26 Oct 63	17:00:00.1	12	1	Shot Report	
ROCKVILLE DAM	39.4N	106.5W	03 Apr 66	16:21:33.6	9	8	Shot Report	
GASBUGGY	36.7N	107.3W	10 Dec 67	19:30:00.1	15	15	Shot Report	
RUL I SON	39.4N	107.9W	10 Sep 69	21:00:00.1	12	8	Shot Report	
PILE- DRIVER	37.2N	116.0W	02 Jun 66	15:30:00.1	13	12	Shot Report	

DISCUSSION

In Table III location errors in latitude and longitude are combined to give errors in kilometers from the true location. The entries in the column giving the best model are determined by consideration of location error, origin time error, and station residuals. Origin time errors in the form of $^{\rm T}$ calc $^{\rm -T}$ true are given in Table IV.

3.1 Location Accuracy with P and P g

Comparing location and origin time errors of runs with $P_n + P_g$ and with P_n only, one notes that the location accuracy with P_s is only about 30% better. The result is not clearly significant and suggests that the addition of P_g to the existing P_n arrivals may not help to improve location.

The best result, an error of 6.31 km, was obtained using crustal epicenter models and $P_n + P_g$. The average origin time error 1.31 seconds is high for this model. The average errors using the Herrin model and P_n arrivals are 8.41 km and 0.53 sec. The average location errors in Table III show that, using proper models the accuracy of event location with P_n and P_g is about 6 to 8 kilometers, or approximately equal to the location accuracies using teleseismic P.

Average location errors using regional models (10 to 11 km) are higher than errors using an epicenter model (6 to 8 km). Location errors using local models (7 to 8 km) are comparable to average errors using the Herrin model (-8 km) but with better origin time errors.

These results show that an accurate source model which is correct for portions of all paths, or local station models which correctly handle the upcoming ray at each station, give good results. The implication is that several models are needed for each path to attain excellent results: a source model for the down-going ray, a receiver model for the up-coming ray, and a path model to give the average propagation velocity. However, the present program is designed for only one model per path.

In an attempt to minimize the effect of crustal variations, Herrin and Taggart (1962) computed an average $P_{\hat{n}}$ velocity and an average crustal thickness for each individual path. The crustal velocity was assumed fixed through-

TABLE III Location Errors, km

Va	rious Mod	Various Models For Each	ch Station			One Mode	One Model For All Stations	tations			
	Local Models	fodels	Regional Models	Models	Herrin	rin	Epicenter Region Model	nter Model	J-B	Best	Kenarks
Name	n + P	u u	9 + P	ď	4 + 4 8 + 14	d.	P + P g	d d	9 + P	Hode	* Largest Kesiduals
PASSAIC	8.40	9.41	8.40	10.06	7.80	58.85	2.59	3.05	2.36*	HE P +	89 A.
DORMOUSE	8.95	5.21	10.97	8.03	9.18	8.75	5.23	1.39	3.95*	n I43	
BANDICOOT	6.12	6.32	15.91*	16.26	11.91	12.90	10.23	68.6	6.14	Local P +	60 60
ROANOKE	4.48	5.79	17.51*	19.29	7.55	8.33	6.71	6.92	5.33	Local P +	os d.
KLIKITAT	99*9	7.10	6.03	8.23	58.9	96*8	04.70	80.4	5,80*	RPI P	
MERRIMAC	NA	7.43	NA	6.20	NA	10.28*	NA	8.16	09*9	REG Pn	No P Phases
FAULTLESS	4.48	2.26	16.41	21.57	15.09	18.30	14.45	18.41	18.80*	Local Pn	
SHOAL	13.74*	13.63	65.9	6.50	5.90	5.88	3.17	3.20	2.06	+ u Id3	P Only 1 P Phase
ROCKVILLE DAM	NA	ΝΑ	8.44	6.64	5.54	5.08	5.17	6.37	14.62*	EPI Pn+	Local models not available for all sta- tions
CASBUGGY	NA	NA	6.79	7.64	3.87	5.20	9.39	13.02	12.63*	HE P +	: 8
RULISON	NA	УA	5.99	6.46	5.84	7.32	67*5	56*9	*11*5	+ u 1d3	" g
PILEDRIVER	NA	NA	10.45	15.84	6.83	4.04	2,33*	21.10	42.24	HE P	ż
Average Error	7.55	5.14	10.32	11.06	79.2	8,41	6.31	8.54	10.39	+ d Id3	8 d
	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	100,100	Mat sent teach of consense and mental man and a label and] [1-1-	10110	£				

NA Not applicable because local models not available for all stations

TABLE IV

Origin Time Errors, Sec, (T_{calc} - T_{true})

		Remarks						No P Phases		Unly 1 P Phase	Local models not available for all sta- tions	=	=	=	
	Least Residual Model		d	9 + P	8 + u	8 u d	8 + u	۵.۳	a. C	ď	ď	u d	<u>م</u> د	ď.	
			EPI	EPI	Local	HE	Local	143	Local	EP.1	EP1	HE	EPI	표	
	J-B	8 + u	- 0.86	- 0.93	89*0 -	- 0.56	- 1.34	- 0.95	0.22	- 1.40	- 1.40	- 2,70	- 2.71	0.80	1.21
For All Stations	Epicenter Region Model	۵. ۵	1.24	1.37	1.72	1.74	1.16	1.25	2.52	06.0	1.10	- 2.10	0.01	1.21	1,36
1	Epic Region	8 + u	1.24	1.47	1.82	1.84	1.36	NA	2.62	06.0	1.40	- 1.60	0.19	00.0	1.31
Une Model	Herrin	u d	- 0.16	- 0.27	- 0.72	0.44	0.16	0.25	1.52	00.00	1.50	09.0	0.49	0.30	0.53
	Нет	8 + u	- 0.16	0.17	0.72	0.54	90.0	NA	1.50	00.00	1.40	0.50	0.49	- 0.30	0.53
G	Models	a, E	77.0	0.17	1.22	2.14	1.26	0.85	2.22	- 0.10	1.10	0.20	- 0.51	1.80	1.00
Each Station	Regional Models	8 4 u d + d	75.0	0.57	1.42	2.24	1.36	NA	2.22	- 0.10	1.40	0.50	- 0.41	09.0	1.03
dels For	Local Models	d u	95.0 -	- 0.83	- 0.48	- 0.26	- 0.14	0.25	0.02	- 0.50	NA	NA	NA	NA	0.37
Various Models For Each	Local	Pa + Pg	- 0.36	- 0.33	- 0.38	- 0.06	- 0.04	NA	0.02	- 0.40	NA	A.	N.	УA	0.23
		Name	PASSIAC	DORMOUSE	BANDICOOT	ROANOKE	KLIKITAT	MERRIMAC	FAULTLESS	SHOAL	ROCKVILLE DAM	GASBUGGY	RULISON	PILEDRIVER	Average of ABS Errors

NA Not applicable because local models not available for all stations

out the path. We feel that this does not yield a complete solution to the problem because travel time variations due to crustal thickness at source und receiver are much greater than travel time variations due to differences in P_n velocity. For example, assume a particular source-to-receiver path across the adjacent Basin and Range (B & R) and Colorado Plateau (CP) regions where the ray travels through 250 km of B & R and 250 km of CP upper mantle. The difference in P_n velocities between these regions is .1 km/sec, i.e. 7.9 for B & R and 7.8 for CP (Table I); therefore, if one model were used, the error in P travel time would be 0.4 second. On the other hand, using the thicknesses of the B & R crust (30 km) and the CP crust (40 km) and an average crustal velocity of 6.6 km/sec for both (Table I), it can be seen that the shortest one-way surface-to-mantle travel time is 1.6 seconds longer for the CP than for the B & R. Thus using one model in this case would mean an error of at least 1.6 seconds in the crustal travel time while the error resulting from the incorrect P_n velocity would be a quarter of that at 0.4 second. This example demonstrates that the effect of the P_n velocity on location accuracy is smaller than the effect of the variations in crustal structures. This also demonstrates why using regional models appropriate to the path but not to the crustal structure under the station may not improve locations.

3.2 Summary and Recommendations for Future Research

The location method used in this study was only marginally successful in improving location accuracy. This is mainly due to the heterogeneity of the crust in the western United States (WUS). The method should produce better results in an area where lateral crustal variations are not as severe as those in the WUS. The reported success in calibrating teleseismic P with the master event method (Chiburis and Ahner, 1970) may not hold with respect to locations with crustal phases because of the stronger effect of lateral heterogeneity on these phases. How accurately the models we used reflect actual crustal conditions is open to question but this is a matter outside the scope of this study.

 $\rm P_g$ observations proved not to be as helpful as expected in improving location accuracy perhaps because the onset of this phase is obscured by coda. Consequently, $\rm P_n$ and $\rm P_g$ should not be weighted equally in computing locations but each observation should be weighted as a function of estimated residual variance.

These results show that deviations from the actual structure in crustal models used for event locations contribute significantly to location errors. We therefore recommend that future effort be directed towards improving model structures rather than forcing observed data to fit some given model.

ACKNOWLEDGEMENTS

We thank Drs. R. R. Blandford and Z. Der for many useful discussions and suggestions. We also thank Anne O'Donnell and Jim Burnetti, who did all of the film analysis for this study.

REFERENCES

- Chiburis, E. F. and R. O. Ahner (1970), A seismic location study of station anomalies, network effects, and regional bias at the Nevada Test Site, Teledyne Geotech, Seismic Data Laboratory Report No. 253, Alexandria, Virginia.
- Engdahl, E. R. and W. H. K. Lee (1976), Relocation of local earthquakes by seismic ray tracing; J. Geophys. Res., 81, 4400-4406.
- Herrin, E. and J. Taggart (1962), Regional variations in P_n velocity and their effect on the location of epicenters, <u>Bull. Seism. Soc. Am.</u>, 52, 1037-1046.
- Julian, B. (1973), Extension of standard event location procedures, Seismic Discrimination SATS, Lincoln Laboratory, M.I.T., 30 June 1973, 4-9.
- Lee, W. H. K and J. C. Lahr (1975), HYPO71 (Revised): A computer program for determining hypocenter, magnitude, and first motion pattern of local earthquakes; USGS Open-file report 75-311, Menlo Park, California.
- McCowan, D. W. (1978), personal communication.
- McCowan, D. W. and R. E. Needham (1978), The use of crustal phases in locating explosion epicenters, Seismic Discrimination SATS, Lincoln Laboratory, M.I.T., 9 June 1978, 1-2.
- McCowan, D. W. and R. E. Needham (1978), Calibration of the Basin and Range with NTS crustal-phase data; Seismic Discrimination SATS, Lincoln Laboratory, M.I.T., 9 June 1978, 6.
- Pakiser, L. C. and R. Robinson (1966), Composition of the continental crust as estimated from seismic observations, The Earth Beneath the Continents, Geophysical Monograph # 10, 620-626, American Geophysical Union.